PATENT ABSTRACTS OF JAPAN

(11)Publication number:

06-155099

(43) Date of publication of application: 03.06.1994

(51)Int.Cl.

B30B 15/04

(21)Application number : **04-309867**

(71)Applicant: KOMATSU LTD

(22)Date of filing:

19.11.1992


(72)Inventor: ARAKI YASUHIRO

(54) PRESS

(57) Abstract:

PURPOSE: To improve the transportability of a large press so that a crown can be transported without being divided.

CONSTITUTION: The press body 1 consists of a bed 2, an upright 3, an upper frame 4 and a crown 5 in which a slide driving mechanism 8 is incorporated, the bed 2 and the upper frame 4 are connected by a tie rod 6 inserted in the upright 3, further, the upper frame 4 and the crown 5 are connected by another tie rod 9 and a slide cuide 4a guiding the slide moved vertically by the slide driving mechanism 8 is mounted on the upper frame 4. Since the crown 5 can be made smaller and more lightweight by mounting the rigid upper frame 4, the transportation can be executed easily.



LEGAL STATUS

[Date of request for examination]

03.08.1999

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration] [Date of final disposal for application]

[Patent number] 3342062

[Date of registration] 23.08.2002

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

* NOTICES *

Japan Patent Office is not responsible for any damages caused by the use of this translation.

- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2. **** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

CLAIMS

[Claim(s)]

[Claim 1] The press which comes to prepare slide-guide 4a which guides the slide 7 which moves up and down with the above-mentioned slide drive 8 while constituting the main part 1 of a press from crown 5 which carried out the interior of a bed 2, aplite 3, the up frame 4, and the slide drive 8, and joining together by the tie rod 6 which inserted in between a bed 2 and the up frames 4 in aplite 3 and combining between the up frame 4 and crown 5 by another tie rod 9 in the above-mentioned up frame 4.

[Translation done.]

* NOTICES *

Japan Patent Office is not responsible for any damages caused by the use of this translation.

- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.**** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

DESCRIPTION OF DRAWINGS

[Brief Description of the Drawings]

[Drawing 1] It is explanatory drawing of the conventional press.

[Drawing 2] It is the vertical section front view of the press which becomes one example of this invention.

[Drawing 3] some presses which become one example of this invention -- it is a notch side elevation [Description of Notations]

1 [-- Aplite, 4 / -- An up frame, 4a / -- A slide guide, 5 / -- Crown, 6 / -- A tie rod, 8 / -- A slide drive, 9 / -- Tie rod.] -- The main part of a press, 2 -- A bed, 3

[Translation done.]


* NOTICES *


Japan Patent Office is not responsible for any damages caused by the use of this translation.


- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.**** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

DRAWINGS

[Drawing 1]







[Translation done.]